



AXCELLA A11 5W-30

Premium performance full synthetic engine oil

Product Overview

AXCELLA A11 SAE 5W-30 is a full synthetic lubricant for ultimate engine protection and performance. It has been designed for modern and sports cars with engines that run faster and hotter in order to achieve maximum power, fuel economy and reduced emissions. It is suitable for the latest Ford engines requiring a WSS -M2C-913C or D lubricant.

Benefits

- Enhanced thermal and oxidation stability
- Extended drain and low oil consumption
- Enhanced frictional properties for improved fuel economy and increased power
- Excellent low temperature properties
- High viscosity index and shear stability

Applications

- Recommended for use in all vehicles including high performance, turbo-charged gasoline and diesel passenger cars fitted with advanced computer controlled multi-valve fuel injection engines
- Suitable for automobiles, light trucks and vans operating in driving conditions requiring a high level of performance
- Suitable for vehicles requiring a WSS-M2C-913 C or WSS-M2C-913D

Health and Safety

This lubricant is unlikely to produce any significant health or safety hazard when used in the application it has been designed for and according to the recommendations provided in the Material Safety Data Sheet. MSDS are available upon request through your sales advisor.

When disposing of used oil, please observe all current regulations and protect the environment.

AXCELLA A11 5W-30

Meets or exceeds the following industry Specifications

API SL	✓
ACEA A5/B5	✓
Ford WSS-M2C-913C & Ford WSS-M2C-913D	✓
Renault RN 700	✓

Typical properties **5W-30**

Test parameters	Method	
Viscosity @ 40 °C, cSt	ASTM D 445	52.4
Viscosity @ 100 °C, cSt	ASTM D 445	9.5
Viscosity Index	ASTM D 2270	176
Flash Point, °C	ASTM D 92	220
Pour Point, °C	ASTM D 97	-39
Density @ 15 °C, Kg/l	ASTM D 4052	0.848
TBN, mg KOH/g	ASTM D 2896	10.1

Above characteristics are mean values given as information. They do not constitute a specification.