



AXCELLA A3 PETROL

Monograde Engine Oil

Product Overview

AXCELLA A3 PETROL SAE 40 is a monograde motor oil suitable for gasoline engines.

Properties and Performances

- Its good detergent dispersant properties effectively minimize formation of lacquer, varnish, sludge and other engine deposits. Hence the oil helps prevent ring sticking and keeps piston clean, while maintaining potential deposits in suspension.
- It is resistant to deterioration, especially that caused by oxidation resulting from prolonged high temperature operation in the presence of air and other agents.
- Its antifoam properties prevent the formation of air bubbles which could adversely affect lubricant film continuity.
- Its special formula ensures superior performance. This reduces combustion chamber deposits, thus lessening the danger of preignition.

Health and Safety

This lubricant is unlikely to produce any significant health or safety hazard when used in the application it has been designed for and according to the recommendations provided in the Material Safety Data Sheet. MSDS are available upon request through your sales advisor.

When disposing of used oil, please observe all current regulations and protect the environment.

AXCELLA A3 PETROL SAE 40

Meets or exceeds the following industry Specifications

API SF/CF	✓
-----------	---

Typical properties **SAE 40**

Test parameters	Method	
Viscosity @ 40 °C, cSt	ASTM D 445	161
Viscosity @ 100 °C, cSt	ASTM D 445	15.7
Viscosity Index	ASTM D 2270	100
Flash Point, °C	ASTM D 92	245
Pour Point, °C	ASTM D 97	-21
Density @ 15 °C, kg/l	ASTM D 1298	0.89

Above characteristics are mean values given as information. They do not constitute a specification.