



ENDURO D2 DIESEL SAE 40

High performance monograde engine oil

Product Overview

ENDURO D2 DIESEL SAE 40 is a high-performance, monograde oil formulated for diesel engines. It is suitable for turbocharged and intercooled engines operating under mild conditions.

Benefits

- Excellent resistance to carbon deposits at high temperature
- Excellent oil thickening and sludge formation control at low temperature
- Suitable with diesel fuels up to 1 wt% sulphur
- Increases anti-oxidant, anti-wear and anti-corrosion properties
- Excellent protection against segment sticking
- High alkalinity reserve with a fresh oil BN of 10

Applications

- Heavy duty turbocharged and naturally aspirated engines
- Light utility and heavyweight vehicles
- Off-road and Off-highway equipment engines, mining and quarrying operations

Health and Safety

This lubricant is unlikely to produce any significant health or safety hazard when used in the application it has been designed for and according to the recommendations provided in the Material Safety Data Sheet. MSDS are available upon request through your sales advisor.

When disposing of used oil, please observe all current regulations and protect the environment.

ENDURO D2 DIESEL SAE 40

Meets or exceeds the following industry Specifications

API CF/SF	✓
Caterpillar TO-2	✓
MIL-L-2104D	✓

Typical properties **SAE 40**

Test parameters	Method	
Viscosity @ 40 °C, cSt	ASTM D 445	144
Viscosity @ 100 °C, cSt	ASTM D 445	14.4
Viscosity Index	ASTM D 2270	95
Flash Point, °C	ASTM D 92	>230
Pour Point, °C	ASTM D 97	-9
Density @ 15 °C, Kg/m3	ASTM D 4052	896
TBN, mg KOH/g	ASTM D 2896	10.2

Above characteristics are mean values given as information. They do not constitute a specification.