



# ENDURO D4 15W-40

High protection multigrade engine oil

---

## Product Overview

ENDURO D4 SAE 15W-40 is a premium commercial multipurpose engine oil formulated to meet the severe service demands of modern diesel and gasoline automotive engines. It provides outstanding protection against oil thickening, high temperature engine deposits, sludge build-up, oil degradation and corrosion.

---

## Benefits

- Good thermal and oxidation stability
- Good control of high temperature deposits
- Improved low temperature sludge control in stop-and-go service
- Reduced oil consumption due to improved high temperature performance

---

## Applications

- Naturally aspirated and turbo-charged diesel engines
- On-highway light and heavy-duty trucking
- Off-highway diesel powered equipment

## Health and Safety

This lubricant is unlikely to produce any significant health or safety hazard when used in the application it has been designed for and according to the recommendations provided in the Material Safety Data Sheet. MSDS are available upon request through your sales advisor.

When disposing of used oil, please observe all current regulations and protect the environment.

ENDURO D4 SAE 15W-40		
Meets or exceeds the following industry Specifications		
API CF-4/CF/SL		✓
Typical properties		SAE 15W-40
Test parameters	Method	
Viscosity @ 40 °C, cSt	ASTM D 445	145
Viscosity @ 100 °C, cSt	ASTM D 445	19.1
Viscosity Index	ASTM D 2270	130
Flash Point, °C	ASTM D 92	220
Pour Point, °C	ASTM D 97	-24
Density @ 15 °C, Kg/l	ASTM D 4052	0.889
TBN, mg KOH/g	ASTM D 2896	8.1

Above characteristics are mean values given as information. They do not constitute a specification.