



ENDURO D5 TURBO 15W-40

High protection multigrade engine oil

Product Overview

ENDURO D5 TURBO SAE 15W-40 is a high-performance diesel engine oils that provide outstanding protection in severe engine applications. They offer maximum engine durability and extended oil drain to a wide range of equipment in the trucking, mining, construction and agricultural industries requiring an API CH-4 oil. Their specific formulations make them suitable for use in gasoline engines as well.

Benefits

- Good thermal and oxidation stability
- Reduce engine deposits & sludge build up
- Superior anti-wear system for optimal protection
- High detergency power to clean the engine and extend its service life
- High viscosity index
- Excellent high and low temperature protection in severe driving conditions

Applications

- Naturally aspirated and turbo-charged diesel engines
- On-highway light and heavy-duty trucking
- Off-highway industries including : construction, mining, quarrying and agriculture

Health and Safety

This lubricant is unlikely to produce any significant health or safety hazard when used in the application it has been designed for and according to the recommendations provided in the Material Safety Data Sheet. MSDS are available upon request through your sales advisor.

When disposing of used oil, please observe all current regulations and protect the environment.

ENDURO D5 TURBO SAE 15W-40

Meets or exceeds the following industry Specifications

API CH-4/CG-4/CF/SL	✓
ACEA E2/A3/B3	✓
MB 228.3	✓
MAN M3275-1	✓
Volvo VDS	✓
MTU Type 2	✓
MACK EO-L	✓
ALLISON C4	✓

Typical properties **SAE 15W-40**

Test parameters	Method	
Viscosity @ 40 °C, cSt	ASTM D 445	145
Viscosity @ 100 °C, cSt	ASTM D 445	14.5
Viscosity Index	ASTM D 2270	130
Flash Point, °C	ASTM D 92	220
Pour Point, °C	ASTM D 97	-24
Density @ 15 °C, Kg/l	ASTM D 4052	0.889
TBN, mg KOH/g	ASTM D 2896	8.7

Above characteristics are mean values given as information. They do not constitute a specification.