



MATIC ATF

High Performance Automatic Transmission Fluid

Product Overview

MATIC ATF is a high-performance fluid for automatic and mechanical gearboxes in passenger cars and light trucks requiring a Dexron® III-H / III-G / II-D level of performance, or in vehicle power-steering systems. It is also appropriate for certain hydraulic applications of farming equipment and other applications with similar requirements.

Benefits

- Good thermal stability and resistance to oxidation
- Good anti-wear-and-tear properties
- Flows extremely well at low temperatures
- Excellent resistance to oxidation

Applications

- Mechanical gearboxes requiring ATF Dexron® III-H / III-G / II-D
- Automatic transmission systems/gearboxes
- Hydrostatic gearboxes
- Power-steering systems
- Industrial hydraulic systems and their components

Health and Safety

This lubricant is unlikely to produce any significant health or safety hazard when used in the application it has been designed for and according to the recommendations provided in the Material Safety Data Sheet. MSDS are available upon request through your sales advisor.

When disposing of used oil, please observe all current regulations and protect the environment.

MATIC ATF		
Meets or exceeds the following industry Specifications		
General Motors Dexron® III-H / III-G / II-D		✓
Ford Mercon		✓
Ford ESP-M2C166-H, Ford ESP-M2C138-CJ		✓
MB p236.2		✓
Allison C-4		✓
CAT TO-2		✓
Typical properties		
Test parameters	Method	
Colour	Visual	Red
Viscosity at 40 °C, cSt	ASTM D445	60
Viscosity at 100 °C, cSt	ASTM D445	7.0
Viscosity Index	ASTM 2270	150
Flash point, °C	ASTM D 92	>180
Pour point, °C	ASTM D 97	-30
Density at 15 °C kg/m3	ASTM D 4052	875

Above characteristics are mean values given as information. They do not constitute a specification.