



# TRANS FLUID

High Performance Hydraulic Oil

---

## Product Overview

TRANS FLUID is a high performance hydraulic oil (SAE 10W) formulated for the lubrication of hydraulic equipment in a wide range of on and off-highway hydraulic applications requiring a CAT TO-2 or Allison C4 performance level.

TRANS FLUID is suitable for gear boxes, torque converters, hydraulic systems when the manufacturer requires an engine oil with an appropriate grade for these applications.

---

## Benefits

- Good detergency and dispersancy level
- Excellent antioxidant, antirust and antifoaming properties

---

## Applications

- Gear Boxes
- Torque converters
- Hydraulic systems on mobile equipment

## Health and Safety

This lubricant is unlikely to produce any significant health or safety hazard when used in the application it has been designed for and according to the recommendations provided in the Material Safety Data Sheet. MSDS are available upon request through your sales advisor.

When disposing of used oil, please observe all current regulations and protect the environment.

**TRANS FLUID**

**Meets or exceeds the following industry Specifications**

Grade	10W
Caterpillar TO-2	✓
Allison C4	✓

**Typical properties** **10W**

Test parameters	Method	
Viscosity @ 40 °C, cSt	ASTM D 445	41.0
Viscosity @ 100 °C, cSt	ASTM D 445	6.2
Viscosity Index	ASTM D 2270	97
Flash Point, °C	ASTM D 92	210
Pour Point, °C	ASTM D 97	-21
Density @ 15 °C, Kg/M3	ASTM D 1298	878

Above characteristics are mean values given as information. They do not constitute a specification.